# LUM-COB RGBW

**LOCATION:** TYPE: **PROJECT:** 



#### **CONTROL OPTION**

- RGBW Controls
  - Requires Adaptive Driver + Smart Receiver
- **DMX Controls** 
  - Requires Adaptive Driver + DMX Receiver
- RGBW In-line Controller

# **FEATURES**

COB tape light features uniform illumination without the need for additional diffused covers or accessories. Featuring a premium seamless line of light making it an ideal solution for areas with low clearance or reflective surfaces to eliminate virtually all dotting or spot-glare effects.

- Seamless RGB+white color mixing capability.
- Wattage output available In 4.87W/ft.
- Cuttable every 2".
- 17.5' foot max run.
- IP20 rating featuring nano-coating protective layer (Standard).
- 50,000 hours rated life.

#### **QUICK SPECIFICATION**

**VOLTAGE**: 24V **WATTAGE**: 4.57W / ft LUMENS: Up to 426 Lm / ft

CCT: RGB + Warm White (3000K/4000K/6500K)

**CUTTING POINTS**: ~ 2" (50mm)

IP RATING: IP20 - Standard, IP67 - Silicon Tube

**DIMMING**: 5-100%

**CERTIFICATIONS**: cULus Listed - Dry / Damp Location


RATED LIFE: 50,000 Hours

### **DIMENSIONS**





on The Top



# **FIXTURE RATINGS & CERTIFICATIONS**











#### **ORDERING KEY** 2 3 5 6 12 1 4 8 10 11 3 - VOLTAGE 5 - LED OUTPUT - LED QTY (pcs/ft) - CUT POINT (in)- MAX RUN (ft) 1 - MODEL # 2 - LENGTH 4 - CCT 6 - IP RATING **RGB+3000K** IP20 - Standard LUM-COB 2 - 2 ft OP1 (24V) - 4.87 W/ft - 170 pcs/ft - 2" - 17.5 ft MAX **24V DC** RGB+4000K IP67 - Silicon Tube **RGBW** 4 - 4 ft **RGB+6500K** 6 - 6 ft 8 - 8 ft **10** - 10 ft COMMENT X'-X" - CSTM

## **LUMIYO TAPE LIGHT SERIES QUICK SET-UP GUIDE**

T: 203-881-6062

